

## TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

### BRAYT T11 POLISHING COMPOUND >silicone free<



#### PRODUCT DESCRIPTION

Brayt T11 polishing compound contains high quality polishing minerals which guarantees quick elimination of defects and high gloss. Because of optimized bonding does not burn in during polishing while being easy to clean. It's universal product suitable for each type of gelcoat, PU and PE lacquers in automotive, furniture industry and composite materials.

#### PHYSICAL AND CHEMICAL PROPERTIES

|            |  |
|------------|--|
| Capacity:  | 1kg. ; 4,5 kg.                               |
| Density:   | 1,5 kg/l                                     |
| Viscosity: | >20,5 mm <sup>2</sup> /s (40 <sup>0</sup> C) |
| Color:     | white  |
| pH:        | > 7  |



March 2015

#### USAGE

- Apply compound on the surface or applicator (foam or lambswool).
- Spread compound on the surface by machine with minimum RPM.
- Slowly increase the speed to max. 1800 RPM and polish surface with medium pressure.
- Polish surfaces until the scratches have been removed gradually reducing the speed and pressure.

#### STORAGE

Product works best when its temperature is 15 – 25<sup>0</sup>C.

Storage in sealed container at 0 – 45<sup>0</sup>C.

#### WARRANTY PERIOD

24 months from production date.

---

**TROTON Sp. z.o.o**

**Address:** Ząbrowo 14A, 78-120 Gościno, Poland, **Tel:** +48 94 35 123 94  
**Tel/Fax:** +48 94 35 126 22 **Website:** [www.troton.com.pl](http://www.troton.com.pl) **Email:** [troton@troton.com.pl](mailto:troton@troton.com.pl)