

**SAFETY DATA SHEET****FILLER 2007 VOC 2.1****1. SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION**

Manufacturer/Distributor

**TROTON Sp. z o. o.**

78-120 Gościno

Ząbrowo, 14A, Poland

Tel./Fax: + 48 94 35 126 22

Tel.: + 48 94 35 123 94

E-mail: troton@troton.com.pl

Emergency telephone number: + 48 94 35 12394**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical name	CAS Number	Content (weight%)
talc	14807-96-6	40-44
titanium dioxide	13463-67-7	0-1
synthetic amorphous silica	112945-52-5	7-8
parachlorobenzotrifluoride	98-56-6	19-20
xylene	123-86-4	3-4
carbon black	1317-65-3	0-2
n-butylacetate	123-86-4	10-11
Aceton	67-64-1	5-6

**3. HAZARD IDENTIFICATION**

HMIS III RATING

Health: 2 $\square$  Flammability: 3 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicate high hazard.

EMERGENCY OVERVIEW

WARNING

COMBUSTIBLE LIQUID

HARMFUL IF INHALED

HARMFUL IF INHALED CAUSE LIVER DAMAGE

CAN CAUSE KIDNEY DAMAGE

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

INGESTION MAY CAUSE GASTRIC DISTURBANCES

POTENTIAL HEALTH EFFECTS

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute toxicity:

Inhalation may cause CNS depression, blurred vision, dizziness and drowsiness.

Inhalation causes headache and nausea.

Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Information on:

Information on:

Information on:

Irritation:

Skin contact may result in irritation, defatting and dermatitis. Vapors cause irritation to the respiratory tract and the eyes.

Prolonged inhalation of product vapor can result in irritation of the mucous membranes.

Repeated dose toxicity:

Information on: n-butyl acetate

Information on: xylene

## 4. FIRST-AID MEASURES

### General advice:

Remove contaminated clothing. Contact the local poison control center.

### If inhaled:

Keep patient calm, remove to fresh air.

If breathing difficulties develop, aid in breathing and seek immediate medical attention.

### If on skin:

Wash affected areas with water for at least 15 minutes. If irritation develops, seek medical attention.

### If in eyes:

Flush with copious amounts of water for at least 15 minutes. Hold eyelids open to facilitate rinsing.

Seek medical attention.

### If swallowed:

Rinse mouth and then drink plenty of water.

Do not induce vomiting due to aspiration hazard.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Immediate medical attention is required.

Ingestion may cause irritation of the gastrointestinal tract.

Aspiration may result in chemical pneumonitis, which may be fatal.

## 5. FIRE FIGHTING MEASURES

Flash point: 25.0 °C

Lower explosion limit: no data

Upper explosion limit: no data

Suitable extinguishing media:

Dry extinguishing media

Carbon dioxide

Foam

Unsuitable extinguishing media for safety reasons: Water spray

### Hazards during firefighting:

Vapors and/or decomposition products are irritants and/or toxic. If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Protective equipment for firefighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Flash fire may occur.

Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat.

Do not flood burning material with water due to potential spreading of fire.

Contain contaminated water/firefighting water. Run-off water from fire may cause pollution. Notify proper authorities.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions:

Extinguish sources of ignition nearby and downwind. Wear suitable personal protective clothing and equipment. Ensure adequate ventilation. Avoid prolonged inhalation. Avoid contact with skin and eyes.

### Environmental precautions:

Do not discharge into drains/surface waters/groundwater. A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities. Acutely toxic for aquatic organisms.

### Cleanup:

Dike spillage. Place into appropriately labeled waste containers. Spills should be contained, solidified, and placed in suitable containers for disposal.

## 7. HANDLING AND STORAGE

### HANDLING

#### General advice:

Ensure adequate ventilation.

Do not puncture, drop or slide containers.

Use static lines when mixing and transferring material. Handle and open container with care.

Avoid contact with the skin, eyes and clothing.

**WARNING:** Empty containers may still contain hazardous residue. Do not apply to hot surfaces.

Proper ventilation and respiratory protection is required when

sanding, flame cutting, welding or brazing coated surfaces.

#### Protection against fire and explosion:

Use antistatic tools.

Exhaust fans should be explosion proof.

Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources.

Sealed containers should be protected against heat as this results in pressure build-up.

Risk of explosion if heated under confinement.

Avoid all sources of ignition: heat, sparks, or open flame.

## STORAGE

### General advice:

Keep container tightly closed.

Protect from direct sunlight. Consult local fire marshal for storage requirements.

### Storage incompatibility:

General: Segregate from incompatible substances. Segregate from oxidizing agents.

Segregate from strong bases.

Segregate from strong acids.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS See section 2.

### PERSONAL PROTECTIVE EQUIPMENT

#### Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear NIOSH-certified (or equivalent) organic vapor respirator.

Particulate filters should be added during spray operations. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

Use appropriate chemically resistant gloves as determined by an evaluation of glove performance characteristics and the hazards and potential hazards identified, including but not limited to butyl, natural and synthetic rubber, nitrile, or neoprene.

#### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

#### Body protection:

Body protection must be chosen based on activity level and exposure.

#### General safety and hygiene measures:

Work place should be equipped with a shower and eye wash. Contact lenses should not be worn. Remove contaminated clothing. Contaminated equipment or clothing should be cleaned after each use or disposed of. Hands and/or face should be washed before breaks and at the end of the shift.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: liquid

Odour: of xylene

Colour: White, Light Grey, Black

Boiling range: no data

Vapour pressure: no data

Density: 1,6 kg/l

Vapour density: heavier than air

Solids content: approx. 68 %

volatiles: approx. 32 %

## 10. STABILITY AND REACTIVITY

Conditions to avoid: Avoid all sources of ignition: heat, sparks or open flames. Avoid electrostatic discharge.

Substances to avoid: Strong bases Strong oxidizing agents Strong acids

Hazardous reactions: This product is chemically stable.

Decomposition products: Carbon monoxide Carbon dioxide

No data.

## 11. TOXICOLOGICAL INFORMATION

No data

## 12. ECOLOGICAL INFORMATION

No data

## 13. DISPOSAL CONSIDERATIONS

Waste disposal of substances:



Dispose of in accordance with national, state and local regulations. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA.

Do not discharge into drains/surface waters/groundwater. Incinerate or dispose of in a RCRA licensed facility. Do not incinerate closed containers.

Contaminated packaging:

WARNING: Empty containers may still contain hazardous residue. Dispose of in accordance with national, state and local regulations.

#### 14. TRANSPORT INFORMATION

Land transport

USDOT

Proper shipping name: Paint

Hazard class: 3

ID-number: UN 1263

Packing group: III

Sea transport

IMDG

Proper shipping name: Paint

Hazard class: 3

ID-number: UN 1263

Packing group: III

Air transport

IATA/ICAO

Proper shipping name: Paint

Hazard class: 3

ID-number: UN 1263

Packing group: III

#### 15. REGULATORY INFORMATION

FEDERAL REGULATIONS

TSCA, US released / listed

STATE REGULATIONS

SARA 313:

CAS number Weight% Chemical name

1330-20-7 5,8% xylene

67-64-1 5-6 %acetone

123-86-4 10-11% n-butylacetate

State RTK:

CAS Number Chemical name

14807-96-6 talc

13463-67-7 titanium dioxide

112945-52-5 synthetic amorphous silica

98-56-6 parachlorobenzotrifluoride

123-86-4 n-butylacetate

1330-20-7 xylene

1317-65-3 calcium carbonate

1333-86-4 carbon black

California Proposition 65 information:

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

#### 16. OTHER INFORMATION

Recommended use: FOR PROFESIONAL USE ONLY .

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION,

# MASTER

DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.