

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier:** V2012 HS 4:1**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Paints and varnishes. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o.
 Zabrowo 14A
 78-120 Goscino - Zachodniopomorskie - Polska
 Phone.: +48 94 35 123 94 -
 Fax: +48 94 35 126 22
 troton@troton.com.pl
 www.troton.pl

1.4 Emergency telephone number: (czynny od 8:00-16:00)+48 094 35 123 94; 112**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture:****CLP Regulation (EC) n° 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:**CLP Regulation (EC) n° 1272/2008:****Warning****Hazard statements:**

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 3: H335 - May cause respiratory irritation

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor

P302+P352: IF ON SKIN: Wash with plenty of water

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH208: Contains Methyl methacrylate. May produce an allergic reaction

Substances that contribute to the classification4-chloro-*o,o*-trifluorotoluene; Xylene (mixture of isomers); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7**2.3 Other hazards:**

VOC=2.0 g/l

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.1 Substance:

Non-applicable

3.2 Mixture:**Chemical description:** Mixture composed of chemical products**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 98-56-6 EC: 202-681-1 Index: Non-applicable REACH:01-2119857280-40-XXX X	4-chloro-α,α,α-trifluorotoluene Regulation 1272/2008 Self-classified Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	10 - <25 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH:01-2119485493-29-XXX X	Butyl Acetate Regulation 1272/2008 ATP CLP00 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	5 - <10 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH:01-2119488216-32-XXX X	Xylene (mixture of isomers) Regulation 1272/2008 Self-classified Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	2,5 - <5 %
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH:01-2119486773-24-XXX X	Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 Regulation 1272/2008 ATP ATP01 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	1 - <2,5 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH:01-2119489370-35-XXX X	Ethylbenzene Regulation 1272/2008 ATP ATP06 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	1 - <2,5 %
CAS: 80-62-6 EC: 201-297-1 Index: 607-035-00-6 REACH:01-2119452498-28-XXX X	Methyl methacrylate Regulation 1272/2008 ATP CLP00 Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	<1 %
CAS: 141-32-2 EC: 205-480-7 Index: 607-062-00-3 REACH:01-2119453155-43-XXX X	n-butyl acrylate Regulation 1272/2008 ATP CLP00 Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	<1 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

- CONTINUED ON NEXT PAGE -

V2012 HS 4:1**SECTION 4: FIRST AID MEASURES (continued)**

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- Precautions for safe manipulation**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	Year
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	50 ppm	100 ppm	2015
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	50 ppm	100 ppm	2015
	221 mg/m ³	442 mg/m ³	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	100 ppm	200 ppm	2015
	442 mg/m ³	884 mg/m ³	
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	2 ppm	10 ppm	2015
	11 mg/m ³	53 mg/m ³	

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4-chloro- <i>a,a,a</i> -trifluorotoluene CAS: 98-56-6 EC: 202-681-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,025 mg/m ³	Non-applicable
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	13,67 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	208 mg/m ³	208 mg/m ³
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	11 mg/m ³

DNEL (General population):

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4-chloro- <i>a,a,a</i> -trifluorotoluene CAS: 98-56-6 EC: 202-681-1	Oral	Non-applicable	Non-applicable	0,2 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,255 mg/m ³	Non-applicable
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	74,3 mg/m ³	104 mg/m ³

PNEC:

Identification				
4-chloro- <i>a,a,a</i> -trifluorotoluene CAS: 98-56-6 EC: 202-681-1	STP	0,032 mg/L	Fresh water	0,002 mg/L
	Soil	0,0258 mg/kg	Marine water	0,0002 mg/L
	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,0216 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00216 mg/kg
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	STP	10 mg/L	Fresh water	0,94 mg/L
	Soil	1,47 mg/kg	Marine water	0,94 mg/L
	Intermittent	0,94 mg/L	Sediment (Fresh water)	5,74 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	STP	3,5 mg/L	Fresh water	0,00272 mg/L
	Soil	1 mg/kg	Marine water	0,00027 mg/L
	Intermittent	0,011 mg/L	Sediment (Fresh water)	0,0338 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00338 mg/kg

8.2 Exposure controls:**A.- General security and hygiene measures in the work place**

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



B.- Respiratory protection

Safety data sheet



According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2008/AC:2009 EN 1149-5:2008	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance: Fluid

Colour: Colourless

Odour: Characteristic

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	137 °C
Vapour pressure at 20 °C:	872 Pa
Vapour pressure at 50 °C:	4420 Pa (4 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	2 kg/m ³ (ISO 1183)
Relative density at 20 °C:	1,556
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	35 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	258 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	
4-chloro- α,α,α -trifluorotoluene CAS: 98-56-6 EC: 202-681-1	LD50 oral	13000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	LD50 oral	4000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.6 mg/L (96 h)	Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	1 - 10 mg/L (96 h)		Fish
	EC50	1 - 10 mg/L		Crustacean
	EC50	1 - 10 mg/L		Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	LC50	191 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	69 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	170 mg/L (96 h)	Selenastrum capricornutum	Algae
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	LC50	5.2 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	230 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	5.5 mg/L (96 h)	Selenastrum capricornutum	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BOD5	0.19 g O2/g	Concentration	Non-applicable
	COD	0.44 g O2/g	Period	Non-applicable
	BOD5/COD	0.43	% Biodegradable	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94,3 %
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	0.56	% Biodegradable	61,3 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	BCF	7
	Pow Log	1.38
	Potential	Low
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	BCF	37
	Pow Log	2.36
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
4-chloro- <i>a,a,a</i> -trifluorotoluene CAS: 98-56-6 EC: 202-681-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,144E-2 N/m (-273,15 °C)	Moist soil	Non-applicable
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
Methyl methacrylate CAS: 80-62-6 EC: 201-297-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,551E-2 N/m (25 °C)	Moist soil	Non-applicable
n-butyl acrylate CAS: 141-32-2 EC: 205-480-7	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,598E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

- CONTINUED ON NEXT PAGE -

V2012 HS 4:1

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Special regulations: 163, 367, 640E, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 37-14:

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN1263
14.2 UN proper shipping name:	PAINT
14.3 Transport hazard class(es):	3
Labels:	3
14.4 Packing group:	III
14.5 Dangerous for the environment:	No
14.6 Special precautions for user	
Special regulations:	163, 223, 955
EmS Codes:	F-E, S-E
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



14.1 UN number:	UN1263
14.2 UN proper shipping name:	PAINT
14.3 Transport hazard class(es):	3
Labels:	3
14.4 Packing group:	III
14.5 Dangerous for the environment:	No
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2012 HS 4:1**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H335: May cause respiratory irritation

H315: Causes skin irritation

H226: Flammable liquid and vapour

H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.