

## TECHNICAL INFORMATION

PRODUCT FOR PROFESSIONAL USE ONLY

### addsTROTON ACRYL CLEAR COAT

#### PRODUCT DESCRIPTION

One-component clear coat spray made from high quality acrylic resin. This product allows to get a quick-drying, highly durable coating resistant to weather conditions.

#### PHYSICAL AND CHEMICAL PROPERTIES

Color:	colorless
Gloss grade:	available mat and gloss
Capacity:	400 ml
Yield:	1 – 2 m <sup>2</sup> / 400 ml
Resin:	Pure Acrylic Resin
Solids:	10 – 25 % (m/m)
VOC:	650 g./l. (appr.)
Density:	0.85 – 0.95 kg./l.
Thinner :	Acetone
Opacity:	1 to 2 layers (depending on the film thickness)
Film thickness :	50 to 100 µm wet (depending on the wanted structure)
Drying time in 20°C:	
✓ Dust dry:	5 – 8 min. (appr.)
✓ Tack free:	60 min. (appr.)
✓ Hard dry:	24 hours (appr.)

Note: Drying time depending on the weathering.

**APPLICATION**

- Clean the surface carefully, dry and degrease.
- Cover the parts which should not be painted.
- Shake before using for 2 – 3 minutes and try it on cardboard.
- Spray paint on the surface from a distance of approx. 25 cm.
- Spray one or two thin layers (as needed).
- After use clean aerosol's outlets – hold down aerosol's valve, push the bottom and release contents for 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

**STORAGE**

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

**WARRANTY PERIOD**

3 years from the production date.