

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON ML transparent CAVITY WAX

PRODUCT DESCRIPTION

One- component product based on wax and impregnates, designed to protect closed profiles of car-body (eg. doors, bonnets, sills) from corrosion . It has good penetrating properties into the gaps and displaces of the surfaces moisture. Creates a flexible, airtight coating that protect against water and salt. It doesn't react with painted surfaces.

PHYSICAL AND CHEMICAL PROPERTIES

- Colour: transparent
- Capacity : 1 liter
- Density*: 0,85 – 0,89 kg/l
- Viscosity: 20 seconds (Ford cup 4 mm.)
- Efficiency: approx. 0,2 kg/m² for 100 µm wet layers
- Temperature resistance: -25 to 160°C

Drying time

- Touch dry*: 90 - 120 min. (± 100 µm)
- Completely dry*: 4 – 6 h. (± 100 µm)

* temp. 20°C, RH 65%

VOC CONTENT

VOC = 450,9 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

USAGE

- Surface to be treated must be clean, dry, degreased, free from dust and rust.
- Shake the can well before use.
- Product can be applied on closed profiles by underbody coating gun with air-pressure of 3-6 bar.
- Used equipment can be cleaned with solvents straight after use. After curing product can be removed only mechanically.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight. Best storage temperature : 10 to 30°C.

WARRANTY PERIOD

24 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

addsTROTON ML amber CAVITY WAX

PRODUCT DESCRIPTION

One- component product based on wax and impregnates, designed to protect closed profiles of car-body (eg. doors, bonnets, sills) from corrosion . It has good penetrating properties into the gaps and displaces of the surfaces moisture. Creates a flexible, airtight coating that protect against water and salt. It doesn't react with painted surfaces.

PHYSICAL AND CHEMICAL PROPERTIES

- Colour: amber
- Capacity : 1 liter
- Density*: 0,85 – 0,89 kg/l
- Viscosity: 20-25 seconds (Ford cup 4 mm.)
- Efficiency: approx. 0,1 kg/m² for 100 µm wet layers
- Temperature resistance: -25 to 80°C

Drying time

- Touch dry*: 90 - 120 min. (± 100 µm)
- Completely dry*: 2 – 3 h. (± 100 µm)

* temp. 20°C, RH 65%

VOC CONTENT

VOC = 402,1 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

USAGE

- Surface to be treated must be clean, dry, degreased, free from dust and rust.
- Shake the can well before use.
- Product can be applied on closed profiles by underbody coating gun with air-pressure of 3-6 bar.
- Used equipment can be cleaned with solvents straight after use. After curing product can be removed only mechanically.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight. Best storage temperature : 10 to 30°C.

WARRANTY PERIOD

24 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

*adds*TROTON ML SPRAY

PRODUCT DESCRIPTION

One-component , wax-based product designed to create anticorrosion protect in cavity areas of car-body (eg. Doors, bonnets, sills etc.). Product has very good penetrating properties and is water-repellent. After drying creates elastic, tight protective coating resistant to harmful effect of weather condition, water, salt and weak acids.

It doesn't react with painted surfaces.

PHYSICAL AND CHEMICAL PROPERTIES

Colour:	amber, transparent
Glass grade:	mat
Volume:	400 ml
Drying time:	approx. 2 – 4 h. / 20 ⁰ C

VOLITARE AND CHEMICAL PROPERTIES

VOC for mixture= 574 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product

USAGE

- Best processing temperature 15 – 25⁰C. Aerosol should have room temperature.
- Shake before using for 2 minutes and try it on cardboard.
- Apply the waxcoating in several layers.
- Remove excess material with mineral spirits.
- **After use clean aerosol's outlets** – hold down aerosol's valve, push the bottom and release contents for 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date, provided the storage condition.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland