

## TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

# TROTON SPRAY FADE OUT THINNER

### PRODUCT DESCRIPTION

High quality spray solution intended for smoothing out of color tone transitions between lacquers after local repairs. It allows an regular transition from the old layer of lacquer to new.

### PROPERTIES

- Quick dry
- Smoothes the surface
- Practical to use
- Capacity: 150 ml.
- Colour: colourless

### USAGE

Shake well before use. Apply thin layers in a contact points of the old paint coat and the newly applied paint. Apply immediately after application of the last layer of lacquer.

Caution : This technical information show the procedure for lacquers made by TROTON company. Details of the other lacquers specified in the relevant technical data sheet.

**VOC CONTENT**

VOC = 730,2 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

**WARNING**

To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

**STORAGE**

Product should be stored in dry, cool, ventilated place, away from fire and direct sunlight.

**WARRANTY PERIOD**

10 years from the production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.  
Ząbrowo, Poland.