

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY BUMPER PAINT structure



PRODUCT DESCRIPTION

Product is based on acrylic resins and cellulose resins. Designed for bumpers and other made of plastic external elements. Spray allows get fine-grained structure, imitating plastic, eliminating small defects of surface. Product is characterized by short drying time and good adhesion, can be sprayed directly on plastic with no need to use primer. Can be covered (spraying) by paint used universally for bumpers.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: black
- Glass grade: mat to semigloss (depending on layer thickness)
- Capacity: 500 ml.
- Density: 0,75 g/ml

Drying time (in temp 20⁰C) :

- Dust dry – after approx.. 15 min
- Tack free – after approx.. 30 min

Note: Drying time depends on air temperature, humidity and thickness of the layer.

VOLATILE COMPONENTS CONTENT

VOC = 574,6 [g/l]

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat. B/5) at the level of 840[g/l] for the ready product.

USAGE

- Surface to be treated should be dry, clean, free of oil and grease.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25÷30 cm distance from the surface.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

3 years from production date.