

MATERIAL SAFETY DATA SHEET

Prepared according to the Decree of European Council no. 1907/2006 from 18.12.2006 regarding registering, evaluation, certification and authorizations in range of chemicals (REACH), creation of European Chemicals Agency, changing Directive 1999/45/EC and cancelling decree of Council no. 793/93 and decree of Commission no.1488/94, as well as directives 76/769/EC, 91/155/EC, 93/67/EC, 93/105/EC and 2000/21/EC.

SECTION 1 IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING1.1. Product identifier:**MATT**1.2. Relevant identified uses of the substance or mixture and uses advised against:

Professional repairs of car body repairs.

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Distributor

TROTON Sp. z. o. o.

78-120 Gościno

Ząbrowo, 14A, Poland

Tel./Fax: + 48 94 35 126 22

Tel.: + 48 94 35 123 94

E-mail: troton@troton.com.pl

1.3.1. Responsible person; E-mail: troton@troton.com.pl

1.4. Emergency telephone number: + 48 94 35 126 22 (from 8:00 am – 4:00 pm)**SECTION 2 IDENTIFICATION OF THREATS**2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

Irritating (Xi)**Extremely flammable (F+)**

Risk phrases:

R 12 Extremely flammable

R 36 Irritating to eyes

R 66 Repeated exposure may cause skin dryness or cracking

R 67 Vapours may cause drowsiness and dizziness

Classification according to Regulation (EC) No 1272/2008:

H220 Flammable gases, Hazard Category 1

H315 Skin corrosion/irritation, Hazard Category 2

H318 Serious eye damage/eye irritation, Hazard Category 1

H336 Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis

2.2. Label elements**GHS02****GHS07****DANGER!****GHS05****H-phrases:**

H222 Extremely flammable aerosol.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

P-phrases:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container according to the local regulations

On the container should be placed inscriptions:**H229-** Pressurised container: May burst if heated.**P210-** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P251- Do not pierce or burn, even after use.**P410+P412 -** Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.

Contain: acetone , butan-1-ol

VOC=712g/l**2004/42/WE IIB(e) (840)712**2.3. Information concerning particular hazards for human and environment:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture:

Description	EEC No	CAS No	EU No	(%)	Classification			
					REACH		CLP	
					Hazard symbol	R phrase	Hazard cat.	H phrase
acetone	606-001-00-8	67-64-1	200-662-2	25-50	F Xi	R11 R36 R66 R67	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336
n-butyl acetate	607-025-00-1	123-86-4	204-658-1	12,5-20		R10 R66 R67	Flam. Liq. 3 STOT SE 3	H226 H336
propane	601-003-00-5	74-98-6	200-827-9	10-12,5	F+	R12	Flam. Gas 1 Press. Gas	H220 H280
2-methoxy-1-methylethyl acetate	607-195-00-7	108-65-6	203-603-9	5-10		R10	Flam. Liq. 3	H226
butane	601-004-00-0	106-97-8	203-448-7	5-10	F+	R12	Flam. Gas 1 Press. Gas	H220 H280
isobutane	601-004-00-0	75-28-5	200-857-2	5-10	F+	R12	Flam. Gas 1 Press. Gas	H220 H280
butan-1-ol	603-004-00-6	71-36-3	200-751-6	2,5-10	Xn Xi	R10 R22 R37/38-41	Flam. Liq. 3 Acute Tox. 4 STOT SE 3 Skin Irrit. 2	H226 H302 H335 H315

						R67	Eye Dam. 1 STOT SE 3	H318 H336
Nitrocellulose	---	9004-70-0	---	1-2,5	F	R11	Flam.Sol.1	H228
propan-2-ol	603-117-00-0	67-63-0	200-661-7	1-2,5	Xi: F:	R36 R11 R67	Flame liq.2 Eye Irit.2 STOT SE 3	H225 H319 H336

Full meaning of phrases and symbols are in section 16.

**Note H (Table 3.1) : The classification and labelling shown for this substance applies to the hazardous property(ies) indicated by the hazard statement(s) in combination with the hazard class(es) and category(ies) shown. The requirements of Article 4 for manufacturers, importers or downstream users of this substance apply to all other hazard classes and categories. For hazard classes where the route of exposure or the nature of the effects leads to a differentiation of the classification of the hazard class, the manufacturer, importer or downstream user is required to consider the routes of exposure or the nature of the effects not already considered.

***Note P :The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures:

Take normal precautionary measures applied during the handling of chemicals. In case of any symptoms, seek medical advice.

IN CASE OF INGESTION:

Measures:

- If swallowed, do not induce vomiting (risk of aspiration).
- Obtain immediate medical help.

IN CASE OF INHALATION:

Measures:

- Remove the affected person to fresh air, keep calm, cover with a blanket.
- In case of shortness of breath, give oxygen.
- If breathing has stopped, administer artificial respiration and obtain medical help.

IN CASE OF SKIN CONTACT:

Measures:

- Immediately flush with plenty of water.
- Take off all contaminated clothing.
- Wash skin with plenty of water and soap.
- In case of symptoms, obtain medical attention and show him the label!

IN CASE OF EYE CONTACT:

Measures:

- Remove contact lenses.
- Flush immediately with plenty of water for 15 minutes, holding the eyelids wide open.
- Consult an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed:

Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

4.3. Indication of any immediate medical attention and special treatment needed:

No special antidote, apply symptomatic treatment.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media:

- 5.1.1. Suitable extinguishing media:
Foam, carbon dioxide or dry chemical.
- 5.1.2. Unsuitable extinguishing media:
Strong water jet.
- 5.2. Special hazards arising from the substance or mixture:
In case of combustion, carbon oxide and toxic fumes are formed.
- 5.3. Advice for firefighters:
Wear full protective clothing (gas-tight and antistatic) and self-contained breathing apparatus.
Cool the fire affected containers with water spray.
Prevent penetration into ground and surface water. Prevent penetration of the fire extinguishing media into ground and surface water. Collect fire extinguishing media separately, do not discharge into sewage system.

SECTION 6 ACCIDENTAL RELEASE MEASURES

- 6.1. Personal precautions, protective equipment and emergency procedures:
 - 6.1.1. For non-emergency personnel:
Keep unprotected people away, allow only well trained experts wearing suitable protective clothing to abide in the field of accident.
 - 6.1.2. For emergency responders:
Remove all ignition sources, flames.
Protect sewage outlets.
Disperse vapours with water spray.
Stop leakage – close the source of the leakage, seal damaged container and place in an other container.
Ensure adequate ventilation.
Wear protective clothing and gloves.
Do not inhale vapours.
- 6.2. Environmental precautions:
Dispose of spillage and waste (product/packaging) in accordance with all applicable environmental laws. Do not allow to enter sewers/soil/surface or ground water. Notify the respective authorities in accordance with local law in the case of environmental pollution immediately.
- 6.3. Methods and material for containment and cleaning up:
Absorb the spilled product with an inert substance (e.g.: sand or diatomaceous earth) and transfer into a sealed container, and send to an authorized waste disposal company. During disposal wear suitable personal protective equipment.
- 6.4. Reference to other sections:
For further and detailed information see section 8 and 13.

SECTION 7 HANDLING AND STORAGE

- 7.1. Precautions for safe handling:
Observe conventional hygiene precautions.
Avoid contact with skin and eyes.
Do not inhale vapours.
Do not eat, drink or smoke during the usage.
Technical measures:
Use only in well-ventilated places with exhaust ventilation.
Tools, equipments and containers must be sealed tightly.
Precautions against fire and explosion:
Keep away from heat and ignition sources.
- 7.2. Conditions for safe storage, including any incompatibilities:
Technical measures and storage condition:
Keep in original, tightly closed and labelled container.
The place of storage has to be properly ventilated and cleanable.
Store in cool and dry place.
Protect against sunlight.
Store below 20°C.
Do not store with self-igniting substances and peroxides.

Store in original, properly labelled containers, which are tightly sealed.
 Do not smoke, eat, use open fire and sparking tools in the place of the storage.
 Keep away from the reach of children.
 Follow all instructions on the label.
 Incompatible materials: strong oxidizing agents.
 Packaging material: original container.

7.3. Specific end use(s):

No specific instructions available.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION8.1. Control parameters:

Substance name	CAS Nr.	8 hours		Short term	
		ppm	mg/m ³	ppm	mg/m ³
acetone	67-64-1	500	1210	1500	3620
n-butyl acetate	123-86-4	150	724	200	966
2-methoxy-1-methylethyl acetate	108-65-6	50	274	100	548
butane	106-97-8	600	1450	750	1810
butan-1-ol	71-36-3	-	-	50	154

8.2. Exposure controls:

In case of a hazardous material with no controlled concentration limit it is the employer's duty to keep concentration levels down to a minimum achievable by existing scientific and technological means, where the hazardous substance poses no harm to workers.

8.2.1 Appropriate engineering controls

In pursuance of work is proper foresight needed to avoid spilling onto clothes and floors and to avoid contact with eyes and skin.

The suction of the vapours at the source(s) of emission and general exhaust ventilation is required. The exhaust vents should be placed in the upper part of the room and at the floor level.

Keep away from heat and ignition sources.

8.2.2. Individual protection measures, such as personal protective equipment:

1. Eye/face protection: use adequate protective goggles.
2. Skin protection:
 - a. Hand protection: use impervious gloves.
 - b. Other: use impervious protective clothes.
3. Respiratory protection: if exposure is likely to exceed the occupational exposure, use approved respiratory protective equipment.
4. Thermal hazard: None known.

8.2.3. Environmental exposure controls:

No specific prescription.

The requirements detailed in Section 8 assume skilled work under normal conditions and usage of the product for appropriate aims. If conditions differ from normal or work is carried out under extreme conditions an expert's advice should be sought out before deciding upon further protective measures.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES:

9.1. Information on basic physical and chemical properties

Physical condition/form colour	Black aerosol
Odour	typical of solvents
Boiling point	No data
Flesh point:	No data
Vapours pressure	No data
Solubility in water and other solvents	Insoluble or poorly soluble
Solubility in organic solvents	soluble
Specific gravity	3500 hPa

pH:	No data
Ignition temperature	No data
Explosive properties: limits	lower: 1,2 vol. %, upper: 13vol. %
Autoignition point	272 °C (522 °F)
Flammable	Hight viscosity liquide, flammable
Explosive properties: limits	Not explosive, no concern
Oxidizing properties	Not oxidizing, no concern
Distribution ratio 1-n-octanol/water	No data available
Other properties:viscosity	No data available

9.2. Other information:
Organic solvent content: 91,9%
Denesty: 0,775 g/cm³

SECTION 10 STABILITY AND REACTIVITY

- 10.1. Reactivity:
None known.
- 10.2. Chemical stability:
Regarding thermal decomposition:
No thermal decomposition if used according to specifications.
- 10.3. Possibility of hazardous reactions:
None known.
- 10.4. Conditions to avoid:
None known.
- 10.5. Incompatible materials:
None known.
- 10.6. Hazardous decomposition products:
Under normal conditions of use, the product does not cause decay.

SECTION 11 TOXICOLOGICAL INFORMATION

- 11.1. Information on toxicological effects:
Acute toxicity: Harmful by inhalation and in contact with skin.
Irritation: None known.
Corrosivity: None known.
Sensitisation: None known.
Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
Carcinogenicity: None known.
Mutagenicity: None known.
Reproduction toxicity: None known.
- 11.1.1. For substances subject to registration, brief summaries of the information derived from the test conducted:
No data available.

- 11.1.2. Relevant toxicological properties of the hazardous substances:
Information on toxicological effects:

<i>Substance</i>	<i>CAS number:</i>	<i>Method/ Value/Unite</i>
n-Butyl acetate	123-86-4	LD ₅₀ (oral, rat): 14 000 mg/kg LD ₅₀ (dermal, rat): > 5 000 mg/kg LC ₅₀ (inhalation, rat): > 51 mg/l/4h
Butan	106-97-8	LC50 (rat) 658 mg/ m ³ /4h
2-Methoxy-1-methylethyl acetate	108-65-6	LD50(oral, rat) 8532 mg/kg LD50(dermal, rat) >5000 mg/kg

- 11.1.3. Information on likely routes of exposure:
ingestion, inhalation, skin and eye contact.
- 11.1.4. Symptoms related to the physical, chemical and toxicological characteristics:
Inhalation: in mild cases it causes cough, irritation of the mouth and throat, sometimes it causes chest pain. In more acute cases it causes headache, vertigo, fatigue, maysthenia, drowsiness and in extreme cases loss of consciousness.

Eye contact: causes mechanical irritation, redness, pain and asthenopia. If the drops of the product get in the eyes, may cause impairment of sight and allergic reactions.

Skin contact: may cause irritation. In case of problematic skin, skin absorption may occur. In case of long term or repeated contact the skin drying and erythroderma may occur. Irritation and redness may occur.

Chronic exposure:

In case of chronic inhalation of the vapour/dust of the product, chest pain, irritation of the mucous membranes, headache, vertigo, excitement or drowsiness, problems with the digestive system, exsiccation, cracking of the skin and allergy may occur.

11.1.5. Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Harmful by inhalation and in contact with skin.

Repeated exposure may cause skin dryness or cracking.

11.1.6. Interactive effects:

No data available.

11.1.7. Absence of specific data:

No information.

11.1.8. Other information:

No data available.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity:

Aquatic toxicity:

Substance:	CAS-number:	Method:	Value:	Unit:
n-Butyl acetate	123-86-4	LC ₅₀ - fish (odmiana złotej rybki)	71	mg/l (48h)
		EC ₅₀ -invertebrate (Daphnia)	72,8	mg/l (24h)
		EC ₅₀ - algae (scenedesmus quadricauda)	21	mg/l (192h)
		EC ₅₀ - bacterium (Pseudomonas putida)	959	mg/l (18h)
		EC ₅₀ - bacterium (niewyspecyfikowane)	>100	mg/l
		UE ₅₀ - bacterium (Photobacterium phosphoreum)	20	mg/l (30min)
Aceton	67-64-1	LC ₅₀ -fish (Leuciscus idus melanotus)	7505-11300	mg/l (48h)
		LC ₅₀ - fish (Salmo gairdneri)	6100	mg/l (24h)
		LC ₅₀ - fish (Poecilla reticulata)	6363	mg/l (14dni)
		LC ₅₀ - fish (Alburnus alburnus)	11000	mg/l (96h)
		LC ₅₀ - invertebrate (Daphnia magna)	>10000	mg/l (24h)
		EC ₅₀ - algae (Anabaena cylindrica)	844	mg/l(14dni)
2-Methoxy-1-methylethyl acetate	108-65-6	LC50(96h)-ryby (Oncorhynchusmykiss)	100-180	mg/l
		EC50(48h)-bezkregowce (Daphnia manga)	>500	mg/l

Effect on activated sludge: at proper entering of small concentrations to biological sewage treatment plants no perturbations should be expected during the decomposition of the activated sludge.

12.2. Persistence and degradability:

Substance	CAS number	Method/ Value/Unite
n-Butyl acetate	123-86-4	Test method: OECD 301D, 92/69/EEC, V. C. 4., activated sludge Analytical method: BOD for the theoretical oxygen demand (ThOD) Degree of degradation: y 90% (28 d) Evaluation: readily biodegradable (according to the OECD criteria)
2-Methoxy-1-methylethyl acetate	108-65-6	Test method: OECD 302B Analytical method: reaction DOC Degree of degradation >90% Evaluation: easy biodegradable

12.3. Bioaccumulation potential:

No data available.

- 12.4. Mobility in soil:
No data available.
- 12.5. Results of PBT and vPvB assessment:
No data available.
- 12.6. Other adverse effects:

Information about the components:

Substance	CAS number	Method/ Value/Unite
n-Butyl acetate	123-86-4	Organically bound halogen subjected to adsorption (AOX). Product does not contain organically bound halogen.

SECTION 13 DISPOSAL CONSIDERATIONS

- 13.1. Waste treatment methods:
Disposal according to the local regulations.
- 13.1.1. Information regarding the disposal of the product:
Do not dispose with communal wastes, do not pour into drainage system. Incinerate in specially adapted installations or deliver to authorized waste collector.
European Waste Catalogue code:
16 05 04* gases in pressure containers (including halons) containing dangerous substances
* hazardous waste.
- 13.1.2. Information regarding the disposal of the packaging
Used packaging should be delivered to authorized collector who has due permission within the range of waste management and especially in dangerous waste management.
European Waste Catalogue code:
For used packaging:
15 01 10* packaging containing residues of or contaminated by dangerous substances
* hazardous waste.
- 13.1.3. Physical/chemical properties that may affect waste treatment options shall be specified:
None known.
- 13.1.4. Sewage disposal:
None known.
- 13.1.5. Special precautions for any recommended waste treatment:
No data available.

SECTION 14 TRANSPORT INFORMATION

Land transport (ADR/RID)

UN Number UN1950
UN proper shipping name AEROSOLS, flammable
Transport hazard class(es) 2.1
Label: 2



Packing group Not applicable
Environmental hazards NO
Tunnel restriction code D


Marine transport IMDG/IMO

UN Number UN1950
UN proper shipping name AEROSOLS, flammable
Transport hazard class(es) 2.1
Label: 2



EmS code F-D, S-U
Packing group Not applicable
Environmental hazards NO

Air transport IATA

UN Number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	2.1
	Label: 2
	
Packing group	Not applicable
Environmental hazards	NO
Special precautions for user	No data available.

SECTION 15 REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:
 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
 COMMISSION REGULATION (EC) No 790/2009 of 10 August 2009 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures
 DIRECTIVE 1999/45/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
 COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- 15.2. Chemical safety assessment: -

SECTION 16 OTHER INFORMATION

Information regarding the revision of the safety data sheet: -

Full text of the abbreviations in the safety data sheet:

DNEL: Derived no effect level. PNEC: Predicted no effect concentration. CMR effects: carcinogenicity, mutagenicity and toxicity for reproduction: PBT: Persistent, bioaccumulative and toxic. . n.d.: not defined. . n.a.: Not applicable. .

Data sources: -

Relevant R-Phrases (number and full text) of Section 2 and 3:

- R10 Flammable
- R11 Highly flammable
- R12 Extremely flammable
- R22 Harmful if swallowed
- R36 Irritating to eyes
- R37/38 Irritating to respiratory system and skin
- R41 Risk of serious damage to eyes
- R66 Repeated exposure may cause skin dryness or cracking
- R67 Vapours may cause drowsiness and dizziness

Relevant H-Phrases (number and full text) of Section 2 and 3:

- Acute Tox. 4 Acute toxicity, category 4
- Eye Dam. 1 Serious eye damage , category 1
- Eye Irrit. 2 Serious eye irritation, category 2
- Flam. Gas 1 Flammable gas, category 1
- Flam. Liq. 2 Flammable liquid, category 2
- Flam. Liq. 3 Flammable liquid, category 3

Press. Gas	Gases under pressure
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity — single exposure, category 3

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H302 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Training instructions: -

Recommended restrictions on use (non-statutory recommendations by supplier): -

This safety data sheet had been prepared on the basis of information provided by the manufacturer. The information, data and recommendations contained herein are provided in good faith, obtained from reliable sources and believed to be true and accurate as of the date issued; however, no representation is made as to the comprehensiveness of the information. The MSDS shall be used only as a guide for handling the product; in the course of handling and using the product other considerations may arise or be required. Since the conditions or the handling, the storage and the disposal of this product are beyond the control of the manufacturer, the distributor or the preparer of this SDS, no warranty, expressed or implied, regarding the product described in this MSDS shall be created or inferred by any statement in this SDS. No responsibility is assumed regarding the accuracy, completeness or suitability of all or any of the information contained herein or the results to be obtained from the use thereof at the time of use. In no way shall the manufacturer, the distributor or the preparer of the be liable for any claims, losses or damages of third parties, personal injury, property damage, lost profits or any special, direct, indirect, incidental, consequential or exemplary damages resulting from the use of or reliance upon such information. Users are cautioned to determine the appropriateness and applicability of the above information to their particular circumstances and purposes and assume all risk associated with the use of this product. It is the responsibility of the user to fully comply with local, national and international regulations concerning the use of this product.